

INSTRUCTIONS FOR COMPLETING APPLICATION FOR MISCELLANEOUS WORK ON TRUNK HIGHWAY RIGHT OF WAY (FORM 1723)

Form 1723 is for miscellaneous minor work activities on trunk highway right of way. It may be used for installation of utility customer service line connections that do not cross or parallel the roadway within the trunk highway right of way. Form 1723 is also used for repair and maintenance of existing utility facilities, installing miscellaneous guy wires and anchors, or tree trimming around utility lines. Form 1723 may also be used to place temporary obstructions on the right of way, to perform temporary relocations to accommodate construction projects, and to place objects on the trunk highway right of way under Minn. Statutes §§160.27 or 173.025.

Fill Out This Form Completely

Print (in ink) or type all information. An incomplete application will delay processing. The form can be filled out online and then printed at: <http://www.dot.state.mn.us/utility/forms.html>

- Be sure to sign it at the bottom. Submit the original form only.
- FAXES ARE UNACCEPTABLE
 - Complete each item on the application. Be specific. If any item does not apply, print "N.A." in the blank.
 - Provide a detailed location of proposed work and give reference to nearest cross streets.
- Include plans of proposed work along with detailed drawings showing type and location of work in relation to MnDOT right of way, on no larger than 11x17 sheets
- Detail any type of traffic interference this work may require and submit a traffic control plan. Detouring of the traffic from the trunk highway will not be permitted, except by special arrangements with the MnDOT District Permit office. All costs involved in the re-routing of traffic including, but not limited to, furnishing barricades, installation or rearrangement of traffic control signs, pavement marking and special flag person services will be charged to the applicant at rates set by MnDOT for the equipment, labor, and materials used.
- Indicate type, kind and size of any object to be placed on trunk highway right of way. Indicate the method of installation and equipment to be used for excavation and compaction.

Submit the complete, signed and dated application (all pages of the form) with the required plans to the MnDOT District Permit office. Contacts and addresses can be found at: <http://www.dot.state.mn.us/utility/districtcontacts.html>

After the Miscellaneous Work Permit has been approved

The applicant will be notified and a security deposit will be required. The permit will have Special Provisions and drawings indicating the construction requirements. Compliance with these instructions during the work operations is mandatory. All Permittees are responsible for the entire costs of their work activities, including proper traffic control. Work cannot be started until all permit and deposit requirements are met and you have received the approved permit.

Security Deposit

A security deposit is required for permits that authorize work in trunk highway right of way to ensure that work is completed to MnDOT's satisfaction. The actual amount required will depend on the specific situation. The District Permit Section will determine the actual amount and type of deposit to be submitted based on the specific situation. Deposits may be in the form of a certified check, cashier's check, or surety bond made payable to "State of Minnesota, Commissioner of Transportation." Deposits must be irrevocable and cannot expire. A permit will not be issued until the required deposit is received.

After construction is completed

The applicant must notify the MnDOT District Permit Office for final inspection. If the construction and all other related work is satisfactory and the turf items are re-established, the deposit will be returned to the applicant. The approved permit is a legal document and should be retained with other valuable papers.



APPLICATION FOR MISCELLANEOUS WORK ON TRUNK HIGHWAY RIGHT OF WAY

Document Management System # _____
 District _____ Permit # _____
 C.S. _____ T.H. _____
 R.P. _____
(THIS SECTION FOR MnDOT OFFICE USE ONLY.)

**ATTACH A SKETCH OF THE PROPOSED WORK AREA AND RELATION TO TRUNK HIGHWAY.
 SUBMIT TO DISTRICT PERMIT OFFICE OF MINNESOTA DEPARTMENT OF TRANSPORTATION.**

APPLICANT	TELEPHONE	ADDRESS (Street, City, State, Zip)
PARTY PERFORMING WORK	TELEPHONE	ADDRESS (Street, City, State, Zip)

LOCATION OF PROPOSED WORK (City/Township) _____ (County) _____ (Distance) _____ (N-S-E-W) _____ **SPECIFIC ROAD INTERSECTION OR LANDMARK**
 Highway _____ in _____ Miles _____ of _____

WILL THIS FACILITY BE WITHIN TRIBAL LANDS? Yes No **IF YES, WHICH ONE?**
NATURE OF WORK

SURFACE TO BE DISTURBED (Check Appropriate Boxes)
 Roadway Shoulder Concrete Bituminous Gravel Turf Only
 Other (explain) _____

DEPTH OF EXCAVATION BELOW SURFACE	NUMBER & SIZE OF EXCAVATIONS	METHOD OF INSTALLATION/CONSTRUCTION
_____	_____	_____
WORK TO START ON OR AFTER	WORK TO BE COMPLETED BY	IS TRAFFIC DETOUR NECESSARY? <input type="checkbox"/> Yes <input type="checkbox"/> No (IF YES, TRAFFIC CONTROL PLAN IS REQUIRED.)

APPLICANT'S ACCEPTANCE, WAIVER AND INDEMNIFICATION

The undersigned applicant hereby agrees to comply with applicable statutes, rules, and the standard conditions and special provisions of this permit. The applicant understands and agrees that no work in connection with this application will be started until the application has been approved and the permit issued.

The applicant is aware of circumstances or hazards that may arise while performing the work associated with this application that could result in injury, loss, damage or death, and the applicant assumes the risk of such circumstances, dangers and hazards, whether reasonably foreseeable or not.

The applicant also understands that this permit may also be subject to the approval of local road authorities having joint supervision over said street or highway, and may be subject to applicant's compliance with the rules and regulations of the Minnesota Environmental Quality Board and/or any other affected governmental agencies.

The undersigned applicant expressly agrees that except for negligent acts of the State, its agents and employees, the applicant or his/her agents or contractor shall assume all liability for, and save the State, its agents and employees, harmless from any and all claims for damages, actions or causes of action arising out of the work to be done in connection with this application and permit.

NAME AND TITLE	EMAIL ADDRESS
_____	_____
DATE	SIGNATURE
_____	_____

DO NOT WRITE BELOW THIS LINE

PERMIT NOT VALID UNLESS BEARING AUTHORIZED MnDOT SIGNATURE AND PERMIT NUMBER

AUTHORIZATION OF PERMIT

It is expressly understood that this permit is conditioned upon restoration of the trunk highway right-of-way to its original condition or to a satisfactory condition. In consideration of the applicant's agreement to comply in all respects with the applicable laws and the conditions of the Commissioner of Transportation pertaining to this permit, permission is hereby granted for the work to be performed as described in the above application, said work to be performed in accordance with the following standard conditions and special provisions:

SEE ATTACHED STANDARD CONDITIONS AND SPECIAL PROVISIONS

_____	_____	_____
Date All Work To Be Completed By	Authorized MnDOT Signature	Date of Authorized Signature

DISTRIBUTION	DEPOSIT REQUIREMENTS	DEPOSIT TYPE
Original to Area Maintenance Engineer	<input type="checkbox"/> No Deposit Required	Cashier's Check # _____
Applicant	<input type="checkbox"/> Deposit Required in the Amount of \$ _____	Certified Check # _____
Subarea Supervisor	Date Deposit Received _____	Money Order # _____
Roadway Regulations Supervisor	<i>Deposit to be returned upon satisfactory completion of all work</i>	Bond # _____

DATE WORK COMPLETED _____ *(The date when the work is completed must be reported to the MnDOT District Permits Office)*

STANDARD CONDITIONS OF MISCELLANEOUS WORK PERMIT

1. The permit holder must comply with all applicable laws and regulations, including Worker's Compensation laws.
2. If work to be done lies within a city or platted town, permission must also be obtained from such city or town.
3. Where work on or near the traveled roadway is necessary, proper traffic signs, channelizing devices, warning lights, and barricades shall be erected to protect traffic, employees, and pedestrians. All traffic control devices and methods shall conform to the Minnesota Field Manual on Temporary Traffic Control Zone Layouts, Minnesota Manual on Uniform Traffic Control Devices (MMUTCD), Minnesota Standard Sign Manual, and the appropriate provisions of Standard Specification 1710.
4. Unless adequately protected by a traffic barrier, there shall be no work within the clear zone, nor shall pipe materials, equipment or other objects be stored within the clear zone as determined by the MnDOT and as defined by the latest edition of AASHTO's "Guide for Selecting Locations, and Designing Traffic Barriers".
5. Excavations must be cribbed when necessary, depending upon type of soil, in order to prevent cave-ins. All excavations, trenching and/or jacking and boring pits shall be shored or sloped in accordance with OSHA requirements.
6. No guys, stays, or any structures are to be attached to trees on trunk highway right of way.
7. No poles, anchors, anchor braces, or other construction shall be placed on the roadway shoulder or within the prescribed clear zone.
8. Installation of pipe under concrete or bituminous pavements shall be done by jacking or boring or other approved methods.
9. When open trenching or excavating in existing roadways, all subgrade, base, and surfacing materials shall be replaced with the same type, depth, and density of materials which were removed, unless approved by the Area Maintenance Engineer.
10. All work that involves trenching, backfill, or compaction must be done to MnDOT's Standard Specifications for Construction. Depending on the construction work to be performed, use of one or more of the following specifications may be needed: Excavation and Embankment 2105, Aggregate Base 2211, Aggregate Shouldering 2221, or Structural Excavation and Backfills 2451, Subgrade Preparation 2112.
Compaction methods must be approved in advance by the District Permit Office
11. If pavement or roadway is damaged, same shall be restored to a condition as good as or better than the original condition.
12. All pavements shall be replaced in accordance with State specifications.
13. If settlement occurs or excavation caves in so that replaced materials settle (bituminous mat or concrete base), same shall be restored to a condition as good as or better than the original condition.
14. No lugs shall be used on equipment traversing the road which will damage the road surface.
15. No driving onto highway from ditch or driving on shoulders will be permitted where damage will occur.
16. No foreign material such as dirt, gravel, or bituminous material shall be deposited or left on the road during any construction activities.
17. Roadside shall be cleaned to original status upon completion of work.
18. Underground construction must be so constructed as not to harm or unnecessarily destroy the root growth of specimen trees.
19. Cutting and trimming of trees within the right of way and removal of resulting stumps require prior approval of the Area Maintenance Engineer or his authorized representative.
20. If MnDOT shall make any improvements or changes upon, over, under, or along the trunk highway, then and in every case the applicant herein named shall after notice from MnDOT proceed to alter, change, vacate, or remove from trunk highway right of way said works necessary to conform with said changes without cost whatsoever to the State of Minnesota.
21. After work on a project is completed, the permit holder must notify the Area Maintenance Engineer or his authorized representative that such work has been completed and is ready for final inspection and acceptance by MnDOT.